



QUICKSHIP PUMP SPECIFICATIONS

MOYNO METERING PUMPS	CEABAMND040008	CEABAMND040009	CEABAMND040010
Moyno Pump Model	B4015D-SSF-3ABA	B4100D-SSF-3ABA	B4190D-SSF-3ABA
Suction Connection Size/Type	1-1/2" FNPT	1-1/2" FNPT	1-1/2" FNPT
Discharge Connection Size/Type	1-1/4" FNPT	1-1/4" FNPT	1-1/4" FNPT
Housing Material	Stainless Steel	Stainless Steel	Stainless Steel
Rotor Material	Chrome Plated 300Series SS	Chrome Plated 300Series SS	Chrome Plated 300Series SS
Stator Material	Fluoroelastomer (VITON)	Fluoroelastomer (VITON)	Fluoroelastomer (VITON)
Seal	Standard Braided Packing	Standard Braided Packing	Standard Braided Packing
Gear Reducer Ratio	2.49:1	2.32:1	2.49:1
Max Flow (Assuming 0-200cps at 5 PSI)	0.12 gpm	0.65gpm	1.2 gpm
Max Discharge Pressure	300 psi	300 psi	300 psi
Temperature Range (F)	50 to 125F		
Motor HP	1 HP	1 HP	1 HP
Motor Speed Range	18 to 1800 RPM (100:1) Turndown - "Motor Rated for 1000:1 Turndown"		
VFD Input Voltage	110-125VAC X 1PH 60HZ - Provided with 10FT Cord with Standard Plug		
VFD information	NEMA 4X Indoor/Outdoor Rated		